



**6" Tablet
Android 9**

Key features

- ◆ IIP65, MIL-STD-810G
- ◆ 4G LTE, WiFi, bluetooth 4.0, GPS
- ◆ NFC, Infrared, 1D/2D barcode scanning
- ◆ Compass, Proximity sensor, Light sensor, Gravity sensor
- ◆ Capacitive multi-touch supports glove touch

Available in Windows 10 IoT Enterprise (E6A)



IP65

HD

4.0

GPS/AGPS

1.2M
DROP

NFC



1D/2D SCANNER

OS

- ◆ Android 9

CPU

- ◆ Qualcomm Cortex A53 2GHz octocore

GPU

- ◆ NA

Memory

- ◆ 2GB DDR3 L (option 4GB)
- ◆ 16GB FlashROM

Display

- ◆ 5.98-inch 720*1280 IPS
- ◆ Gorilla Glass
- ◆ 430 Nits
- ◆ 5-point capacitive touch

RF

- ◆ Wi-Fi 802.11 a/b/g/n/ac
- ◆ Bluetooth V4.0
- ◆ 4GLTE
- ◆ GPS

Camera

- ◆ 5Mpx front camera
- ◆ 13Mpx rear camera with flash and autofocus

Keys

- ◆ Power
- ◆ Volume +/-
- ◆ Barcode scanner trigger
- ◆ Home

Sensor & Data Collection

- ◆ NFC
- ◆ 1D/2D barcode reader
- ◆ Accelerometer
- ◆ Light Sensor

Power Adapter

- ◆ 5V/2.5A

Battery

- ◆ Lithium-Ion Polymer 3.7V - 5000 mA
- ◆ Removable battery

Audio

- ◆ 3.5 mm Audio jack

I/O Interface

- ◆ Micro USB x1
- ◆ Micro TF slot x1
- ◆ Micro SIM slot x1
- ◆ 3.5mm Standard earphone Jack

Dimensions Weight Protection

- ◆ 185 x 94 x 26 mm
- ◆ 360g

Durability

- ◆ IP65
- ◆ 1.2 m drop
- ◆ Shock & vibration
- ◆ MIL STD 810G

Environmental

- ◆ Operating temperature : -10°C to +50°C
- ◆ Storage temperature: -30°C to +70°C

Security

- ◆ NA

Warranty

- ◆ «Continuité» warranty extension total 3 years (return workshops, repair within 10 working days upon receipt of the material - without breakages)
- ◆ «Confort» Contract 3 years, full service contract (include 1 battery swap) / (return workshops, repair within 5 working days upon receipt of the material - with breakages)

Software

- ◆ GMS (Google Mobile Services)

Accessories



1 slot desktop charger
AT-CAE603B



2 slots desktop charger
AT-CAE603



Additional battery E6
AT-CAE601



USB power supply
AT-CAE602



hand strap
AT-CAE604



Holster with belt clip
AT-CAE606



Cigar jack cable charger
AT-CASPA4308



protective screen
AT-CAE605